







Monocrystalline Solar Module



Efficient Controller



Battery system




All-in-One



Everlight LED

IP65




## Our Advantages

#### ABOUT LED



# **Everlight LED**


- 120Lm/W, 30% brighter than other similar products
- Longer working hours, 15% longer than other similar products



# LED Modular System Design

The well optimized light distribution, makes for a more uniform and wider lighting area.






### Much Stronger


Sectional area is 50% larger than others for thicker materials

Much Safer

Keep it much safer with screw

## Bat wing light distribution curve





## **Technical Data**

#### LGA Series All in One Technical Data

### \* Packaging of 1 unit per carton

Model No.		LGA30W
		LGASUW
	Physical Parameters	
LED Brand		Everlight LED
Power of PV Module (W)		60W
LIFEPO4 Battery Capacity (Ah)		24
Dimension of Product (mm)		769*769*267
Net Weight (kg)		16.4
Dimension of Carton (mm)		915*915*322
Gross Weight (kg)		20
Light Parameters		
Light Output (W)		30W
Typical Luminous Flux (Lm)		3600
Color Temperature (K)		2700-6500
Beam Angle (°)		120°
Min. Working Time (Hours)	Full Bright	13
	Dim Mode	39
Env	ironment Parameters	
Charging Temperature (°C)		0 °C to +60 °C
Discharing temperature (°C)		-20 °C to +60 °C
Storage temperature (°C)		-20 °C to +45 °C
Installation		
Recommended Dia. of Top Pole (mm)		
Recommended Installation Height (m)		5~6
Recommended Installation Distance (m)		10~18

להזמנות ופרטים נוספים ניתן לפנות לחברת דרכי האור:

POB 98, Ma'ale Adumim, ISRAEL 9810002 Mobile: 972-50-2500565 Tel: 972-2-6730822 Fax: 972-2-6730892 elikom565@gmail.com

